




**Reference: F01267**

## LINE-E F01267



<b>Lenght (mm)</b>	1192
<b>Width (mm)</b>	60
<b>Depth (mm)</b>	80
<b>System power (W)</b>	40W
<b>Luminous flow (lm)</b>	4000lm
<b>Voltage</b>	200-240V AC
<b>Degree of protection</b>	IP20
<b>Luminaire life (h)</b>	L80 - 50'000H
<b>Driver lifetime (h)</b>	50'000H
<b>Beam angle</b>	50° ↓
<b>Finishing</b>	Argent RAL9006
<b>Light source</b>	Seoul 2835 LEDs
<b>UGR</b>	10
<b>IK resistance</b>	IK05
<b>MacAdam</b>	3
<b>IRC</b>	80
<b>Diffuser</b>	PC
<b>Fixation</b>	Encastré
<b>Driver brand</b>	BOKE
<b>Driver output amperage</b>	800-1000mA
<b>Driver output voltage</b>	6-42V DC
<b>Protection class</b>	Class I
<b>Warranty</b>	5 years
<b>Color temperature</b>	3000K
<b>Light regulation</b>	On-off
<b>Operating temperature</b>	-20°C ~40°C

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.