

Reference: **D33010**

## Tilis 65 D33010



|                              |                       |
|------------------------------|-----------------------|
| <b>Height (mm)</b>           | 157                   |
| <b>Diameter (mm)</b>         | Ø65                   |
| <b>System power (W)</b>      | 10W                   |
| <b>Luminous flow (lm)</b>    | 940lm                 |
| <b>Voltage</b>               | 200 - 240V AC         |
| <b>Degree of protection</b>  | IP20                  |
| <b>Luminaire life (h)</b>    | 50'000                |
| <b>Driver lifetime (h)</b>   | 50'000                |
| <b>Beam angle</b>            | 30°                   |
| <b>Finishing</b>             | Blanc                 |
| <b>Light source</b>          | COB                   |
| <b>IRC</b>                   | >80                   |
| <b>Fixation</b>              | Applique              |
| <b>Matter</b>                | Aluminium / Plastique |
| <b>Warranty</b>              | 5ans                  |
| <b>Color temperature</b>     | 4000K                 |
| <b>Light regulation</b>      | On / Off              |
| <b>Operating temperature</b> | -20? ~40?             |
| <b>Efficiency</b>            | ~94lm/W               |
| <b>Flicker</b>               | Sans scintillement    |
| <b>Weight</b>                | 0,45Kg                |