

Reference: F8449

BubblyB T600 F8449



| | |
|------------------------------|------------------------------|
| Height (mm) | 79 |
| Diameter (mm) | Ø600 |
| System power (W) | 60W max (option 42W / 49W) |
| Luminous flow (lm) | 4950lm |
| Voltage | 220 - 240V AC |
| Degree of protection | IP40 |
| Luminaire life (h) | 50'000 |
| Driver lifetime (h) | 50'000 |
| Beam angle | 85° |
| Finishing | Black |
| Light source | SMD |
| IRC | >80 |
| Diffuser | Prismatic |
| Fixation | Suspension tube |
| CDL type | Direct / Indirect |
| Protection class | Classe I |
| Matter | Aluminium |
| Warranty | 5ans |
| Color temperature | 3CCT : 3000K / 4000K / 5700K |
| Light regulation | Dali |
| Operating temperature | -20°C +40°C |
| Efficiency | 82,5lm/W |
| Notes | Éclairage direct |
| Flicker | Sans scintillement |
| Weight | 3,2Kg |

Sous réserve de modifications techniques car nos produits sont constamment améliorés.
We reserve the right to make technical changes as our products are constantly being improved.
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.